«上一篇/Previous Article|本期目录/Table of Contents|下一篇/Next Article»

Research on the dynamic performance of ship isolator systems that use magnetorheological dampers(PDF)

《船舶与海洋工程学报》[ISSN:1002-2848/CN:61-1400/f] 期数: 2009年04 页码: 291--297 栏目: 出版 日期: 2009-12-25

Title: Research on the dynamic performance of ship isolator systems that use magnetorheological dampers

作者: 邓忠超;姚熊亮;张大刚

- Author(s): DENG Zhong-chao*; YAO Xiong-liang and ZHANG Da-gang College of Shipbuilding Engineering, Harbin Engineering University, Harbin 150001, China
- 关键词: magnetorheological fluid damper; vibration reduction; shock resistance; isolator
- 分类号:

DOI:

文献标识码: A

Isolator systems on ships should ideally be able to simultaneously reduce low 摘要 frequency vibration response and high frequency shock response. Conventional isolator systems are unable to do so. To solve the problem, a new style isolator system was created. This isolator system consists of a steel coil spring component and a magnetorheological (MR) damper component working in parallel. Experiments on this isolator system were carried out, including tests of vibration reduction and shock resistance. The vibration load frequencies were set from 1-15 Hz, and force amplitudes from 2.94~11.76 kN. The maximum shock input acceleration was 20 g, and impulse width was 10ms. Both the vibration and shock loads were applied using MTS Systems Corporation's hydraulic actuators. The experimental results indicated that the isolator system performs well on system vibration response, with resonance humps of the vibration response obviously reduced after using the MR damper. For the shock experiment, the attenuation of shock response was much faster with increased MR damping. The MR damper's effect on shock moments was very different from its performance in vibration mode. The correlation between MR force and control current was not as evident as it was during vibration loads.

参考文献/REFERENCES

[1]OU J P, GUAN X C. Experimental study of magnetorheological damper performance[J]. Earthquake Engineering and Engineering Vibration, 1994, 18(3): 74-81.

[2]GINDER J M, DAVIS L C, ELIE L D. Rheology of magnetorheological fluids: models and measurements[C]// 5th Int. Conf. on ERF, MRS and Their Applications. UK: Univ. Sheffield, 1995: 504-514.

[3]CARLSON J D, WEISS K D. Magnetorheological materials based on alloy particles: U.S. Patent, No 5,382,373[P].1995.

[4]DYKE S J, SPENCER B F, SAIN M K, et al. Seismic response reduction using magnetorheological dampers[C]// Proc. of the IFAC World Congress, San Francisco, CA, 1996: 145-150.

[5]SPENCER B F. Phenomenological model for magnetorheological damper[J]. J Engrg Mech, ASCE, 1997, 123(3): 230-238. [6]PHULE P P, GINDER J M. Synthesis of novel magnetorheological fluids[J]. MRS Bulletin, 1998, 23(8): 23-25.

[7]SIRETEANU T, STANCIOIU D, STAMMERS C W. Use of magnetorheological fluid dampers in semi-active driver seat vibration control[C]//ACTIVE 2002, ISVR. Southampton, UK, 2002.

[8] DUAN Y F, NI Y Q, KO J M. Cable vibration control using magnetorheological dampers[J]. Journal of Intelligent Material Systems and Structures, 2006, 17(4): 321-325. [9]YAO X L. Ship Vibration[M]. Harbin: Harbin Engineering University Publishing Company, 2004: 51-66.

导航/NAVIGATE	
本期目录/Table of Contents	
下一篇/Next Article	
上一篇/Previous Article	
工具/TOOLS	
引用本文的文章/References	
下载 PDF/Download PDF(759K	B)
立即打印本文/Print Now	
推荐给朋友/Recommend	
统计/STATISTICS	
统计/STATISTICS 摘要浏览/Viewed	451
统计/STATISTICS 摘要浏览/Viewed 全文下载/Downloads	451 312
统计/STATISTICS 摘要浏览/Viewed 全文下载/Downloads 评论/Comments	451 312

[10]ZHONG Z. Low-frequency Big-damping and impact-resistance isolator of arch steel wire spring[J]. Ship Engineering, 2005, I5(1): 16-22.

备注/Memo: -

更新日期/Last Update: 2010-05-20