## An Experimental Study on Wind Loads Acting on a Trimaran PCC(PDF)

《船舶与海洋工程学报》[ISSN:1002-2848/CN:61-1400/f] 期数: 2010年02 页码: 121--128 栏目: 出版 日期: 2010-06-25

Title: An Experimental Study on Wind Loads Acting on a Trimaran PCC
作者: 二瓶 泰範; 李 侨; 池田 良穗(
Author(s): Yasunori Nihei; Qiao Li\* and Yoshiho Ikeda
Department of Marine System Engineering, Osaka Prefecture University, Sakai, Osaka,

- 599-8531, Japan
- 关键词: PCC; trimaran; wind pressure; characteristics; estimation method

```
分类号
```

DOI:

## 文献标识码: A

In recent years, demands for car transportation by a ship have been increasing with 摘要 favorable economic conditions in auto sector, and the need of a pure car carrier (PCC) has grown quickly. A PCC needs huge parking space but smaller displacement since a car is comparatively light for its volume. As a result, almost all PCCs have wide breadth, shallow draft and huge structure above the water surface. These features cause some technical issues of a PCC, like lack of stability, effect of strong winds on its resistance, difficulty of course keeping in rough seas, difficulty of berthing in strong winds, and so on. To overcome these technical issues, one of the authors has proposed a new concept for a PCC. This is a trimaran PCC which has very limited transverse bulkheads in the center hull by using two side hulls as fenders. In the present research, wind forces acting on a scale model of the trimaran PCC were measured in the towing tank with a wind generator at Osaka Prefecture University. Furthermore, in order to clarify the characteristics of wind pressure on the trimaran, height and width of tunnels which are between a main hull and side hulls were changed. And then, in order to imitate a real ship, we used wind reduction technology of corner-cut design for accommodation house of the ship. Moreover, the wind pressure acting on the trimaran was compared with that on a mono-hull PCC. Using these experimental and theoretical results, an estimation method of wind pressure acting on the trimaran PCC is deduced.

## 导航/NAVIGATE 本期目录/Table of Contents 下一篇/Next Article 上一篇/Previous Article 工具/TOOLS 引用本文的文章/References 下载 PDF/Download PDF(525KB) 立即打印本文/Print Now 推荐给朋友/Recommend 统计/STATISTICS 摘要浏览/Viewed 657 全文下载/Downloads 469 评论/Comments RSS XML

## 参考文献/REFERENCES

Fujiwara T, Ueno M, Nimura T (2001). An estimation method of wind forces and moments acting on ships. Mini Symposium on Prediction of Ship Manoeuvring Performance, Tokyo, Japan, 83-92. Isherwood RM (1972). Wind resistance of merchant ships. The Royal Institution of Naval Architects, 115, 327-338. Matumoto K, Tanaka Y, Hirota K, Usami S, Takagishi K (2003). Reduction of wind force acting on ships. Journal of the

Kansan Society of Naval Architects, 240, 115-121.

Nihei Y, Mizobe T, Oura T, Ikeda Y (2008). A feasibility study of a new trimaran PCC in medium speed. The 4th Asia-Pacific Workshop on Marine Hydrodymics-APHydro2008, Taipei, 17-23.

Yamano T, Saito Y (1997). An estimation method of wind forces acting on ships. Journal of the Kansai Society of Naval Architects, 228, 91-100. (in Japanese)

更新日期/Last Update: 2010-06-01