

Minimal knotted polygons in cubic lattices

E.J. Janse van Rensburg, A. Rechnitzer

(Submitted on 11 Jul 2011)

An implementation of BFACF-style algorithms on knotted polygons in the simple cubic, face centered cubic and body centered cubic lattice is used to estimate the statistics and writhe of minimal length knotted polygons in each of the lattices. Data are collected and analysed on minimal length knotted polygons, their entropy, and their lattice curvature and writhe.

Subjects: **Statistical Mechanics (cond-mat.stat-mech)**; General Topology (math.GN)Cite as: [arXiv:1107.2162](#) [cond-mat.stat-mech](or [arXiv:1107.2162v1](#) [cond-mat.stat-mech] for this version)

Submission history

From: Andrew Rechnitzer [[view email](#)]

[v1] Mon, 11 Jul 2011 22:51:06 GMT (429kb,D)

[Which authors of this paper are endorsers?](#)

Download:

- [PDF](#)
- [Other formats](#)

Current browse context:

cond-mat.stat-mech

[< prev](#) | [next >](#)[new](#) | [recent](#) | [1107](#)

Change to browse by:

[cond-mat](#)[math](#)[math.GN](#)

References & Citations

- [NASA ADS](#)

Bookmark([what is this?](#))

Science
WISE