

Agricultural Journals

Research in

AGRICULTURAL ENGENEERING

home page about us contact

us

Table of Contents

IN PRESS

RAE 2013

RAE 2012

RAE 2011

RAE 2010

RAE 2009

RAE 2008

RAE 2007

RAE 2006

RAE 2005

RAE 2004

RAE 2003

RAE Home

Editorial

Board

For Authors

- AuthorsDeclaration
- Instruction to Authors
- Guide for Authors
- CopyrightStatement
- Submission

For Reviewers

- Guide for Reviewers
- ReviewersLogin

Subscription

Res. Agr. Eng.

J. Lendelová, Š. Pogran

Thermo-technical

structures for lying cubicles

Res. Agr. Eng., 49 (2003): 146-150

A paper dealing with prevailing floor construction types from a thermo-technical point of view. The accent was put on lying cubicles for cows, the floors must be soft, dry, warm and flexible. Attention was paid to analysis of the thermal resistance and thermal absorptive capacity of selected types of flooring. The greatest thermal comfort depends upon the design of floor structured coating materials. A biological floor accretion layer has a positive thermal influence and softens thermal comfort during the animals lying period. A calculation, estimating values of thermal absorptive capacity, shows that the quality and thickness of the structured layer on a covered floor is very important, underlying layers are only affected with thinner designs of a calculated boundary value.

Keywords:

cow; floor; lying cubicle; thermal comfort; thermal absorptive capacity

[fulltext]

© 2011 Czech Academy of Agricultural Sciences

XHTML1.1 VALID

