

[本期目录](#) | [下期目录](#) | [过刊浏览](#) | [高级检索](#)[\[打印本页\]](#) [\[关闭\]](#)

成像技术与图像处理

TDI-CCD图像固有条带噪声的消除方法及实现

赵变红^{1,2}, 何斌¹, 杨利红^{1,2}, 王文华¹, 禄金波^{1,2}1. 中国科学院 长春光学精密机械与物理研究所, 吉林 长春 130033, E-mail: yunhan0502@gmail.com;
2. 中国科学院 研究生院, 北京 100039**摘要：**

存在于TDI-CCD图像中的条带噪声会影响图像的质量,降低系统的测量精度。针对TDI-CCD图像固有条带噪声的灰度值在原始信息中变化比较缓慢的特点,利用傅里叶变换域内的频谱图映射确定条带噪声频率的方法,分别采用低通、带阻滤波器对条带噪声进行消除。另外,提出了一种改进阈值的小波变换法来消除条带噪声,该方法能在小波分解后各个尺度的垂直方向上自适应地确定阈值。实验结果表明在消除条带噪声方面,改进阈值的小波变换法优于传统的傅里叶变换法。在整个频率域内,改进阈值的小波变换法能够较彻底地消除条带噪声,同时较好地保持了原图像的特征。

关键词： TDI-CCD 条带噪声 傅里叶变换 小波变换 自适应阈值

Methods and Realization for Removing Inherent Stripe Noises in TDI -CCD Images

ZHAO Bian-hong^{1,2}, HE Bin¹, YANG Li-hong^{1,2}, WANG Wen-hua¹, LU Jin-bo^{1,2}1. Changchun Institute of Optics, Fine Mechanics and Physics, Chinese Academy of Sciences, Changchun 130033, China, E-mail: yunhan0502@gmail.com;
2. Graduate School of Chinese Academy of Science, Beijing 100039, China**Abstract:**

The existence of stripe noises influences the qualities of TDI-CCD images, and reduces the measurement accuracy of the system simultaneously. For the characteristic of slow change of the stripe noises' grey level compared with the primary information, the stripe noises are eliminated via low-pass filter and band-elimination filter separately using the method of determining the stripe noise frequency through the frequency spectrum mapping in the Fourier transform domain. Moreover, an improved threshold of Wavelet Transform method of eliminating stripe noise is presented in this paper. The each vertical direction's threshold in various scales is determined by itself after the wavelet decomposition. It is proved that in removing the TDI-CCD stripe noises, the improved threshold of Wavelet Transform is better than the traditional Fourier Transform. The stripe noises can be removed drastically via the improved threshold of Wavelet Transform method, the goal which reserves the spectral characteristic of original image is also achieved.

Keywords: TDI-CCD stripe noises Fourier transform wavelet transform adaptive threshold

收稿日期 2010-01-08 修回日期 2010-02-08 网络版发布日期 2010-09-28

基金项目：

国家“863”高技术研究发展计划资助项目(No.863-2-5-1-13B)

通讯作者：

作者简介：赵变红(1985-),女,河南商丘人,硕士研究生,主要研究方向为空间遥感图像处理方面技术。

作者Email:

参考文献：[1] Horn B K P, Woodham R J. Despeckling landsat MSS imagery by histogram modification [J]. *Comput Graph & Image Process*, 1979, 10: 69-83.[2] Kautsky J, Nichols N K, Jupp D L B. Smoothed histogram modification for image processing [J]. *Comput Vis & Image Process*, 1984, 26: 271-291.[3] Gadallah F L, Csillag F. Despeckling multisensor imagery with moment matching [J]. *INT J Remote Sensing*, 2000, 21(12): 2505-2511.

[4] 刘正军, 王长耀, 王成. 成像光谱仪条带噪声去除的改进矩匹配方法 [J]. 遥感学报, 2002, 6(4): 280-284.

[5] Srinivasan R, Cannon M, White J. Landsat data despeckling using power filtering [J]. *Optical Engineering*, 1998, 27: 939-943.

[6] Simpson J J, Gobat J I, Frouin R. Improved destriping of GOES images using finite impulse response filters
[J]. *Remote Sens. Environ.*, 1995, 52: 15-35.

[7] Simpson J J, Stitt J R, Leath D M. Improved finite impulse response filters for enhanced destriping of geostationary satellite data
[J]. *Remote Sens Environ*, 1998, 66: 235-249.

[8] 杨忠东, 张文建, 李俊, 等. 应用小波收缩方法剔除MODIS热红外波段数据条带噪声
[J]. 遥感学报, 2004, 8(1): 23-30.

[9] 孙颖, 张志佳. 基于频域滤波的自适应条带噪声去除算法
[J]. 仪表技术与传感器, 2006, (2): 57-59.

[10] Donoho D L, Johnstone I M. Ideal spatial adaptation by wavelet shrinkage
[J]. *Biometrika*, 1994, 81(3): 425-455.

[11] 于超, 陈光武, 石文静. 基于FPGA的信号采集及其频谱显示
[J]. 液晶与显示, 2008, 23(4): 499-503.

[12] 何伟, 俞立, 董辉. 基于IWT图像压缩技术的LED同步显示系统设计
[J]. 液晶与显示, 2009, 24(2): 262-267. (上接P723)例:

[12] 西安电子科技大学. 光折变自适应光外差探测方法:中国,01128777.2 .2002-03-06 .<http://211.152.9.47/sipoasp/zljs/hyjs-yx-new.asp?recid=01128777.2&leixin=0>. 电子文献: 主要责任者·题名·其他题名信息 ·出版地:出版者,出版年(更新或修改日期) ·获取和访问路径·例: