search

engineering

science

management

architecture + planning

humanities, arts, and social sciences

campus

multimedia

press


Graphene electrodes for organic solar cells

Researchers identify technique that could make a new kind of solar photovoltaic panel practical.

David L. Chandler, MIT News Office

today's news

Research update: How to tame hammering droplets



This image from a high-speed camera shows a droplet being deposited on a superhydrophobic surface,

just before it separates from the dropper used to deposit it. At the moment of separation, ripples move down through the droplet, revealing the sudden deceleration caused by impact with the surface, which causes a brief burst of high pressure

image courtesy of Kripa Varanasi

MIT research uncovers new process relating to the way drops of water spread after striking a surface.

Putting up a struggle against cancer


January 20, 2011

Prodigy of probability

January 19, 2011

| January 6, 2011 | |
|--|---------|
| email | comment |
| print | share |
| A promising approach for making solar cells that are | |

inexpensive, lightweight and flexible is to use organic (that is, carbon-containing) compounds instead of expensive, highly purified silicon. But one stubborn problem has slowed the development of such cells: Researchers have had a hard time coming up with appropriate materials for the electrodes to carry the current to and from the cells. Specifically, it has been hard to make electrodes using materials that can match the



The structure of graphene, a flexible material made of carbon atoms arranged in a layer just one atom thick, is represented in this diagram. Graphic: Christine Daniloff

organic cells' flexibility, transparency and low cost.

The standard material used so far for these electrodes is indium-tin-oxide, or ITO. But indium is expensive and relatively rare, so the search has been on for a suitable replacement. Now, a team of MIT researchers has come up with a practical way of using a possible substitute made from inexpensive and ubiquitous carbon. The proposed material is graphene, a form of carbon in which the atoms form a flat sheet just one atom thick, arranged in a chicken-wire-like formation.

An analysis of how to use graphene as an electrode for such solar cells was published on Dec. 17 in the journal Nanotechnology, in a paper by MIT professors Jing Kong and Vladimir Bulović along with two of their students and a postdoctoral researcher.

Graphene is transparent, so that electrodes made from it can be applied to the transparent organic solar cells without blocking any of the incoming light. In addition, it is flexible, like the organic solar cells themselves, so it could be part of installations that require the panel to follow the contours of a structure, such as a patterned roof. ITO, by contrast, is stiff and brittle.

The biggest problem with getting graphene to work as an electrode for organic solar cells has been getting the material to adhere to the panel. Graphene repels water, so typical procedures for producing an electrode on the surface by depositing the material from a solution won't work.

The team tried a variety of approaches to alter the surface properties of the cell or to use solutions other than water to deposit the carbon on the surface, but none of these performed well, Kong says. But then they found that "doping" the surface — that is,

multimedia

Video: Vladimir Bulovic on OLED displays

From TechTV

Video: Nanoscale engineering for highperformance solar cells From MIT World

related

Jing Kong

Vladimir Bulović

ARCHIVE: "A material for all seasons "

tags

energy

materials science

solar energy

eni

national science foundation (nsf)

introducing a set of impurities into the surface — changed the way it behaved, and allowed the graphene to bond tightly. As a bonus, it turned out the doping also improved the material's electrical conductivity.

While the specific characteristics of the graphene electrode differ from those of the ITO it would replace, its overall performance in a solar cell is very similar, Kong says. And the flexibility and light weight of organic solar cells with graphene electrodes could open up a variety of different applications that would not be possible with today's conventional silicon-based solar panels, she says. For example, because of their transparency they could be applied directly to windows without blocking the view, and they could be applied to irregular wall or rooftop surfaces. In addition, they could be stacked on top of other solar panels, increasing the amount of power generated from a given area. And they could even be folded or rolled up for easy transportation.

While this research looked at how to adapt graphene to replace one of the two electrodes on a solar panel, Kong and her co-workers are now trying to adapt it to the other electrode as well. In addition, widespread use of this technology will require new techniques for large-scale manufacturing of graphene — an area of very active research. The ongoing work has been funded by the Eni-MIT Alliance Solar Frontiers Center and an NSF research fellowship.

Peter Peumans, an assistant professor of electrical engineering at Stanford University, who was not involved in this study, says organic solar cells will probably become practical only with the development of transparent electrode technology that is both cheaper and more robust than conventional metal oxides. Other materials are being studied as possible substitutes, he says, but this work represents "very important progress" toward making graphene a credible replacement transparent electrode.

"Other groups had already shown that graphene exhibits good combinations of transparency and sheet resistance, but no one was able to achieve a performance with graphene electrodes that matches that of devices on conventional metal oxide (ITO) electrodes," Peumans says. "This work is a substantial push toward making graphene a leading candidate."

Comments

Log in to write comments



MIT news | 77 Massachusetts Avenue, Room 11-400 | Cambridge, MA 02139-4307 | Tel 617.253.2700 | TTY 617.258.9344 twitter | rss | contact | about the mit news office | terms of use | comments | **Massachusetts Institute of Technology**

GIVE TO MIT >>