

## <u>TOP</u> > <u>Available Volumes</u> > <u>Table of Contents</u> > Abstract

ONLINE ISSN : 1881-1698 PRINT ISSN : 1880-8204

## The Journal of Silk Science and Technology of Japan

Vol. 16 (2007) 45-50

[PDF (376K)] [References]

# **Preparation of High performance Activated Carbon from Cocoon with Potassium Carbonate**

Akira KOJIMA<sup>1)</sup>, Teruaki OGAWA<sup>1)</sup>, Masao FUJISHIGE<sup>1)</sup> and Youichi KAMIISHI<sup>2)</sup>

1) Department of Chemistry and Material Science, Institute of Gunma National College of Technology

2) Science and Technology Promotion Division, Gunma Prefecture

(Accepted August 30, 2007)

## Abstract

New usage of cocoon was investigated for applying activated carbon. The largest specific surface area of activated cocoon plate carbon was obtained by a treatment with  $K_2CO_3$  in

the former paper. In order to obtain more large specific surface area, various condition of activation were examined. In this study, the largest value of specific surface area was  $5571 \text{m}^2/\text{g}$ , which was obtained under the condition of heating at 800°C for 1h after immersed in an aqueous solution of K<sub>2</sub>CO<sub>3</sub>. Mean value of micro hole diameter was about 0.5 nm.

## Keywords

activated carbon, activation, cocoon, surface area, pore size distribution

[PDF (376K)] [References]

Download Meta of Article[<u>Help</u>] <u>RIS</u> BibTeX

To cite this article:

Akira KOJIMA, Teruaki OGAWA, Masao FUJISHIGE and Youichi KAMIISHI (2007): Preparation of High performance Activated Carbon from Cocoon with Potassium Carbonate .

The Journal of Silk Science and Technology of Japan, 16, 45-50.

JOI JST.JSTAGE/silk/16.45

Copyright (c) 2009 by The Japanese Society of Silk Science and Technology

