Characteristics of The Fillers Used for Realizing the Asphalt Mixtures in Romania

Author(s): Irina-Mihaela Dămiean • Gh. Gugiuman

Tomme: LI (LV) | **Fascicle:** 3-4 | 2005

Pages: 111-114
Abstract text:

This paper presents the lab results for four types of filler used in producing the asphalt mixture in Romania, as well as other physical-chemical characteristics of a new type of filler, derivate of the grinding of the bituminous shists through a ball mill/crusher. Knowing these physical-chemical characteristics is crucial for asphalt mixtures due to the complex purpose of the filler.

Key Words:

-



Author(s) Information

Irina-Mihaela Dămiean

Affiliation: "Gheorghe Asachi" Technical University, Jassy, Department of Transportation Infrastructure and Foundations.

Email:

Gh. Gugiuman

Affiliation: "Gheorghe Asachi" Technical University, Jassy, Department of Transportation Infrastructure and Foundations. Email: gugiuman@ce.tuiasi.ro

All documents with a 🔁 icon require Adobe Acrobat installed on your computer

Current Issue

T. LVI (LX), Fasc. 3, 2010

Browse by Issues by Authors

For Authors
Preparing Artworks
Manuscript Submission
Manuscript Template
Journals Name Abbreviation
Copyright Transfer Statement

Abstracted & Indexed

The Bulletin of the Polytechnic Institute of Jassy, Construction. Architecture Section is indexed and abstracted in:

Index Copernicus, ProQuest, Ebsco, DOAJ, BASE, Scientific Commons, DRIVER, WorldWideScience.org, getCITED, ResearchGATE, Ovid LinkSolver, Genamics Journalseek, Electronic Journals Library, WorldCat, Intute.

Ranking

The journal is ranked by the National University Research Council as a B+ quality journal (CNCSIS Code 44).

Search in:

