

砂的临界状态本构模型局部化分叉分析

Bifurcation analysis of strain localization by critical state model for sands

中文关键词: [临界状态](#) [本构模型](#) [砂](#) [分叉](#) [数值模拟](#) [平面应变](#)

英文关键词: [critical state](#) [constitutive model](#) [sands](#) [bifurcation](#) [numerical simulation](#) [plane strain](#)

基金项目:

作者	单位
甄文战	上海大学 土木工程系, 上海 200072
孙德安	上海大学 土木工程系, 上海 200072

摘要点击次数: 218

全文下载次数: 59

中文摘要:

基于砂的临界状态本构模型考虑了平均有效应力水平及孔隙比的影响,能合理地反映不同密度和应力水平下砂的变形特性。该模型对平面应变状态下变形局部化分叉的解析表明:在围压一定时,分叉出现在应力应变关系硬化阶段,分叉点对应的应力比及剪切带倾角均随孔隙比的增加而减小;密砂及松砂分叉点对应的应力比分别在临界状态线的上侧和下侧;而且峰值应力比与分叉应力比差值基本不变,但松砂较密砂差值大。在初始孔隙比一定时,密砂分叉点对应的应力比及剪切带倾角随着初始有效围压的增大而减小,而松砂分叉时的应力比及剪切带倾角基本不受围压影响。最后,为了验证解析解的正确性,采用回映应力更新算法,编写了有限元材料子程序,将该模型嵌入有限元软件ABAQUS。通过对多单元立方体试样数值模拟结果与解析解的对比,两者基本一致。

英文摘要:

The occurrence of strain bifurcation is dependent closely on the used constitutive model and values of model parameters. The critical state model for sands can describe the stress-strain behaviour of loose, medium and dense sands, with mean stress level and void ratio being considered. In this paper the bifurcation solutions to a critical state model established by Yao et al (2004) in different initial void ratios and initial confining pressures are obtained. The theoretical analysis shows that, when the initial confining pressure is fixed, bifurcation for medium, dense and loose sands occurs in hardening regime. Bifurcation stress ratio and inclination angle of shear band decreases with increasing initial void ratio, and stress ratio at bifurcation is greater than the slope of the critical state line (CSL) for medium and dense sands, but less than that for loose sands. The difference in stress ratio between peak and bifurcation is almost the same for medium, dense or loose sands, but is greater than that for loose sands. With the initial void ratio being fixed, bifurcation stress ratio and inclination angle of shear bands for medium and dense sands decrease with the increase of initial confining pressure, but they are nearly unchanged for loose sands. Finally, the return mapping algorithm is adopted in order to implement the model into nonlinear finite element analysis software ABAQUS through the user material subroutine (UMAT) interface. The numerical simulation for a cubic specimen at different initial void ratios and confining pressures are carried out, and the results show that the numerical results agree with the theoretical solutions well.

[查看全文](#) [查看/发表评论](#) [下载PDF阅读器](#)

您是第1055470位访问者

主办单位: 中国水利学会 出版单位: 《水利学报》编辑部

单位地址: 北京海淀区复兴路甲一号 中国水利水电科学研究院A座1156室 邮编: 100038 电话: 010-68786238 传真: 010-68786262 E-mail: slxb@iwhr.com

本系统由北京勤云科技发展有限公司设计