



ISSN 1000-6893

CN 11-1929/V



Engineering Village



航空学报 » 2013, Vol. 34 » Issue (2) : 227-234 DOI: 10.7527/S1000-6893.2013.0026

流体力学与飞行力学

[最新目录](#) | [下期目录](#) | [过刊浏览](#) | [高级检索](#)<< ◀◀ [前一篇](#) | [后一篇](#) ▶▶ >>

压力敏感涂料特性及其校准技术实验研究

李国帅¹, 周强¹, 刘祥¹, 金毕青², 高丽敏³, 马护生¹, 熊健¹

1. 中国空气动力研究与发展中心, 四川 绵阳 621000;
2. 武汉工程大学 材料科学与工程学院, 湖北 武汉 430073;
3. 西北工业大学 动力与能源学院, 陕西 西安 710072

Experimental Research of Pressure Sensitive Paint Performance and Calibration Technique

LI Guoshuai¹, ZHOU Qiang¹, LIU Xiang¹, JIN Bqing², GAO Limin³, MA Husheng¹, XIONG Jian¹

1. China Aerodynamics Research and Development Center, Mianyang 621000, China;
2. School of Materials Science and Engineering, Wuhan Institute of Technology, Wuhan 430073, China;
3. School of Power and Energy, Northwestern Polytechnical University, Xi'an 710072, China

[摘要](#)[参考文献](#)[相关文章](#)Download: [PDF](#) (4164KB) [HTML](#) OKB Export: [BibTeX](#) or [EndNote \(RIS\)](#) [Supporting Info](#)

摘要

精细化的校准技术和涂料特性研究是影响压力敏感涂料(PSP)测量技术精度及其工程应用的重要因素。为此以PSP地面实验测量系统为主要平台,进行了国产PSP的静态校准和光降解实验,基于自主编制的PSP静态校准图像后处理程序研究了PSP压力、温度灵敏度之外所展现出的重要特性。研究结果表明:一定压力范围内,PSP的Stern-Volmer响应曲线呈现出较为明显的非线性,在校准中应采取高阶Stern-Volmer关系式进行拟合;在均匀压力和温度下,不同样片区域的校准结果呈现出空间不均匀性,这种不均匀性会影响PSP的校准精度;PSP存在光降解效应,其降解曲线在一定时间内近似为线性。同时,本文还简要分析了其产生机理以及对PSP测量精度的影响,初步提出了相应的评估指标及改进措施。

关键词: 压力敏感涂料 静态校准 涂料特性 压力响应非线性 空间不均匀性 光降解

Abstract:

Calibration technique and paint performance research are critical for improving the measurement accuracy and engineering application of pressure sensitive paint (PSP). In this paper, static calibration and photo-degradation experiments are performed based on a PSP static calibration setup and image post-processing software which is programmed independently to study paint performances other than its pressure and temperature sensitivity. The results of this study reveal that the Stern-Volmer curve of PSP exhibits a nonlinear characteristic rather than following the conventional linear pattern, which is approximated with an polynomial function using curve-fitting analysis. Moreover, calibration results of the painted coupon vary in space although the experiment is performed under uniform pressure and temperature, and it tends to decrease calibration accuracy. Finally, PSP demonstrates a photo-degradation characteristic and the degradation curve is approximately linear within a range of time. Evaluation indices of pressure response nonlinearity, calibration spatial non-uniformity and photo-degradation are proposed while their mechanisms of production, influences on PSP measurement accuracy and correction methods are also presented.

Keywords: pressure sensitive paint static calibration paint performance nonlinear pressure response spatial non-uniformity photo-degradation

Received 2012-02-23; published 2012-06-07

Fund:

国家自然科学基金(11172316)

Corresponding Authors: 周强 Email: zhouqiang6604@163.com

Service

- ▶ 把本文推荐给朋友
- ▶ 加入我的书架
- ▶ 加入引用管理器
- ▶ Email Alert
- ▶ RSS

作者相关文章

- ▶ 李国帅
- ▶ 周强
- ▶ 刘祥
- ▶ 金毕青
- ▶ 高丽敏
- ▶ 马护生
- ▶ 熊健

mail:lgs0000@163.com;周强,男,博士后。主要研究方向:流场测量和流动显示等。Tel:0816-2462463,E-

mail:zhouqiang6604@163.com;刘祥,男,博士研究生,助理研究员。主要研究方向:实验流体力学。Tel:0816-2463920,E-

mail:372792387@qq.com

引用本文:

李国帅, 周强, 刘祥, 金毕青, 高丽敏, 马沪生, 熊健. 压力敏感涂料特性及其校准技术实验研究[J]. 航空学报, 2013, 34(2): 227-234.DOI: 10.7527/S1000-6893.2013.0026

LI Guoshuai, ZHOU Qiang, LIU Xiang, JIN Biqing, GAO Limin, MA Husheng, XIONG Jian. Experimental Research of Pressure Sensitive Paint Performance and Calibration Technique[J]. Acta Aeronautica et Astronautica Sinica, 2013, 34(2): 227-234.DOI: 10.7527/S1000-6893.2013.0026