

## SHORT REPORT

# Determination of Compressibility and In Vitro Release Properties of Acetaminophen Granules Coated with Eudragit E 30 D

Tansel ÇOMOĞLU, Ahmet AYDINLI, Tamer BAYKARA

Department of Pharmaceutical, Faculty of Pharmacy, Ankara University, 06100 Tandoğan, Ankara - Turkey

Received: February 21, 2005

**Key Words:** Acetaminophen, Eudragit E 30 D, compressibility

Acetaminophen is a drug which has a bitter taste and a short biological half life ( $t_{1/2} = 2-3$  hours). There are two metabolites of acetaminophen in the body. The first form is the conjugation of glucuronic acid and the other is the hydrolylated form of the active metabolite. The second, hydroxylated metabolite is hepatotoxic in high concentrations (1,2). In order to avoid this effect, the rate of drug absorption must be slowed down.

In this study, we attempted to prepare acetaminophen granules by coating with a specific taste and odor masking acrylic polymer Eudragit E 30 D with the Fluidized bed process(3). Then, by direct compression method, tablets of these granules were prepared and consolidation and compressibility properties as well as in vitro release studies were investigated.

The acetaminophen particules were coated with fluidized bed (Glatt/Germany) using Eudragit E 30 D (Röhm Pharma GmbH/Germany). 250 g of acetaminophen were weighed. The concentration of the coating material was decided as 0.5 (C1), 3 (C2) and 5 (C3) % and dispersed in 50 ml distilled water. During the process, a nozzle having a diameter of 0.5 mm was used.

The rate of the coating process was 5 ml/minute Eudragit E 30 D dispersion was sprayed 10 times/minute and the pressure of spraying air was 1.5 bar. After each spraying portion, in order to prevent agglomeration, the total amount was dried for 5 minutes at 70°C. After the coating process the whole mass was dried with hot air for

10 minutes. After the coating process of acetaminophen was completed the granules were formulated to prepare tablets.

The tablet formulation used is shown below:

Acetaminophen granules (containing 160 mg acetaminophen)	0.2 g	40 %
Avicel pH 101 <sup>®</sup> (FMC Corp./USA)	0.270 g	54 %
Precirol ATO 5 <sup>®</sup> (Gattefosse/France)	0.005 g	1 %
Ac-Di-Sol <sup>®</sup> (FMC Corp./USA)	0.025 g	5 %

The quantities indicated are calculated for 1 tablet.

The mixing process was done in a cylindrical jar for 10 minutes in the turbula mixer.

### Determination of consolidation properties of granules

The consolidation of 10 ml of each powder mixture was achieved in a 10 ml graduated cylinder with a funnel, so that percolation could be avoided. Then the weight of 10 ml was determined, the bulk density (BD) being calculated thereafter. The graduated cylinder was tapped with the help of the tapping instrument 5, 10, 20, 30, 40, 50, 75, 100, 200 and 300 times and the reduction in volume was measured. The natural logarithm of the tapping values ( $N_T$ ), thus obtained was plotted against double (ln) the relative density change (A) (Equation 1)

and the parameters of the regression were determined with a computer programme (Basic 80) (Figure 1) (4).

$$A = \frac{TD - BD}{TD} \quad \text{(Equation 1)}$$

A: Relative density change

TD: Tapped density

BD: Bulk density




Figure 1. Consolidation of the mass according to Kawakita and Heckel equations.

### Determination of the compressibility of granules

The compression properties of each mixed powder were investigated by using the HECKEL and KAWAKITA equations (5). For this purpose a 10 mm flat-faced punch and a hydraulic press were used. Equal volumes of granules (1357.13 mm<sup>3</sup>) were pressed at 767.0, 1150.5, 1534.0, 1917.5, 2301.0 and 3068.1 kgf/cm<sup>2</sup>. When the desired pressure was reached, it was kept at this value for 20 seconds. The volume of the tablet; V<sub>p</sub>, formed at each pressure level was calculated. Results were calculated with a computer programme written using the Heckel and Kawakita equations (6).

Heckel equation;

$$\ln = \frac{V_p}{V_p - V_\infty} = kP + \frac{V_0}{V_0 - V_\infty} \quad \text{(Equation 2)}$$

V<sub>0</sub>: Initial powder volume

V<sub>p</sub>: The volume at each pressure value

V<sub>∞</sub>: The true volume of the solid (without pores)

k: Constant. Heckel correlated the slope of the compaction curves, k, with the yield strength of the material being compressed (k = 1/P<sub>y</sub>)

Kawakita equation;

$$\frac{V_0 - V_p}{V_0} = \frac{abP}{1 + bP} \quad \text{(Equation 3)}$$

or,

$$\frac{P}{C} = \frac{1}{ab} + \frac{1}{a} \cdot P \quad \text{(Equation 4)}$$

C: Degree of volume reduction (V<sub>0</sub> - V<sub>p</sub> / V<sub>0</sub> = C)

V<sub>0</sub>: Initial apparent volume of powder

V<sub>p</sub>: Powder volume under applied pressure (P)

a,b: Constants, characteristic of the powder

In the Kawakita equation (a) is a numeric parameter indicating the initial porosity of the compressed powder mass and (b) is the compression coefficient.

### In vitro release rate studies

In vitro release rate studies were employed to tablets using USP XXIV, (Method 2) paddle method (37 ± 0.5°C, 50 rpm). pH 5.8 phosphate buffer solution was used as a dissolution medium and 4 ml's of aliquots were withdrawn at each interval and assayed at 241 nm with a Shimadzu UV - VIS 1201 spectrophotometer and dissolution profiles were determined (Figure 2) (7).

When consolidation and compressibility parameters of the formulations were evaluated, C3 gave the best results. In the Heckel equation, the largest r<sup>2</sup> (0.9285) and P<sub>y</sub> (643.9 kgf/cm<sup>2</sup>) values belonged to this formulation (Tables 1, 2). Kawakita's (a) value determined the greatest initial porosity in C3 formulation also.

Table 1. The consolidation parameters.

Formulation code	Slope	Intercept
C1	0.0982	-0.8116
C2	0.1614	-1.0979
C3	0.1338	-1.1223

Table 2. The compressibility parameters according to Heckel and Kawakita equations.

Formulation code	HECKEL		KAWAKITA	
	$r^2$	$P_y$ (kgf/cm <sup>2</sup> )	$r^2$	a
C1	0.9027	257.2	0.9991	-0.9029
C2	0.8548	370.7	0.9992	-0.9808
C3	0.9285	643.9	0.9992	-0.9419

When dissolution rate studies were evaluated, Figure 2 showed us that drug release rate slowed down with the increase in coating thickness (8).

As a result, when acetaminophen particules were coated with different concentrations of Eudragit E 30 D, the consolidation and compressibility parameters were improved when compared to the drug itself. Also release rate of the drug was modified in all formulations when




Figure 2. Dissolution profiles of tablets.  
C\* = Tablet without any coat

compared to the drug itself. Among the three formulations C3, which had Eudragit E 30 D at the highest ratio (5%), gave the best compressibility and release results.

Corresponding author:

Tamer BAYKARA

Department of Pharmaceutical,  
Faculty of Pharmacy,

Ankara University,

06100 Tandoğan, Ankara - Turkey

E-mail: baykara@pharmacy.ankara.edu.tr

## References

- Seong HJ, Min HL, Myung GL. "Pharmacokinetics of acetaminophen after intravenous and oral administration to spontaneously hypertensive rats and normotensive Wistar rats" *J Pharm Sci* 83: 810-814, 1994.
- Brandon G. "Paracetamol overdose: Way forward" *Pharm J*, 252: 804, 1994.
- Röhm Pharma (Eudragit Data Sheet) Röhm GmbH, Darmstadt, Industrial Products Division.
- Beten DB, Yüksel N, Baykara T. "The changes in the mechanical properties of a direct tableting agent microcrystalline cellulose by precompression" *Drug Dev Ind Pharm* 20: 2323-2331, 1994.
- Parrott EL, Lieberman L, Lachman L. (eds.) "Compression in Pharmaceutical Dosage Forms: Tablets", Marcel Dekker Inc New York Vol: 2, 154, 1981.
- Süleyman MM, Baykara T. "A microcomputer programme series for use in tablet technology", presented at the 3<sup>rd</sup> Int. Pharm. Tech. Symposium, Ankara, September 9-11, 89, 1986.
- The United States Pharmacopoeia (USP XXIII) United States Pharmacopoeial Convention Inc, 1620, 1995.
- Rubio MR, Ghaly ES. "In vitro release of acetaminophen from sodium alginate controlled release pellets" *Drug Dev Ind Pharm*, 20, 1239-1251, 1994.