

## Simulation and Prediction for Groundwater Dynamics Based on RBF Neural Network

Zhonghua Fei<sup>1</sup>, Dinggui Luo<sup>2</sup>, Bo Li<sup>1</sup>

<sup>1</sup>School of Mathematics and Physics, Changzhou University, Changzhou, China <sup>2</sup>School of Environmental Science and Engineering, Guangzhou University, Guangzhou, China Email: 32321006@sina.com

Received March 5, 2012, revised April 7, 2012; accepted May 9, 2012

## ABSTRACT

Based on MATLAB, a new model-BRF network model is founded to be used in groundwater dynamic simulation and prediction. It is systematically studied about the training sample set, testing sample set, the pretreatment of the original data, neural network construction, training, testing and evaluating the entire process. A favorable result is achieved by applying the model to simulate and predict groundwater dynamics, which shows this new method is precise and scientific.

Keywords: Dynamic Simulation and Forecast; Groundwater; BP Network; RBF Networks

## **1. Introduction**

That the factors (such as water level, water quantity, water chemical composition, water temperature, etc.) in the aquifer system changing with time under interaction in the surrounding environment, is called groundwater dynamics. Groundwater dynamics is caused by the imbalances of water, heat, energy and salt. The studies on this is of great significance to find out the variation of groundwater resources and the characteristic of reentry and outflow, to guide water intake and drainage project and reasonable exploitation and utilization of groundwater resources, and to solve environmental problems such as ground subsidence, water quality deterioration, saltwater intrusion etc. Therefore, the mathematical model of groundwater dynamics can be divided into deterministic mathematical model and uncertainty mathematical model including numerical method, the fuzzy mathematics method, grey system methods, statistical analysis, Kriging valuations, regression analysis, time series analysis, spectrum analysis (Fourier analysis, wavelet analysis, etc.), and artificial neural network (ANN) method etc.

Compared with the traditional statistical analysis model, neural network model has better durability and timelier forecast and can be used to solve the prediction problem of groundwater system with multiple arguments and multiple dependent variables.

In the present, most researches on neural network apply BP (Back Propagation) network. Although BP algorithm is based on solid theory basis and can be used widely, there are some unsolved problems on it. By in troducing the principles of RBF (Radial Basis Function) network, this paper points out that RBF network has advantageous properties such as independence of the output on initial weight value and adaptation for determining the construction. Using MATLAB as the platform, we apply the network for simulation and prediction of groundwater dynamics and get a good achievement in construction of training set and checking set, pretreatment of original data, and establishment, training, inspection and result evaluation of the neural network.

### 2. The Principle of Radial Basis Network

We will introduce RBF basic principle [1-3], training and its realization methods. The radial basis network is a three-layer feedforward network composed of input layer, hidden and output layer, see **Figure 1** (with a single output neurons as an example) where hidden neurons use radial basis function as activation function, usually with Gaussian function as radial basis function.

Each neuron of the hidden layer inputs the product of the distance between the vectors  $W1_i$  and the vector  $X^q$  multiplied by its own offset value  $b1_i$ . The vector  $W1_i$  is the connected weight value between neuron of hidden layer and of input layer and also known as the *i*th hidden layer neuron function (RBF) center. The vector  $X^q$  represents the *q*th input vector denoted by

 $X^{q} = (x_{1}^{q}, x_{2}^{q}, \dots, x_{j}^{q}, \dots, x_{m}^{q})$ . From the **Figure 2**, we can see that the *i*th neuron input for the hidden layer is  $k_{i}^{q}$ :

$$k_i^q = \sqrt{\sum_j \left(w \mathbf{1}_{ji} - x_j^q\right)^2} \times b \mathbf{1}_i$$



Figure 1. Construction of RBF network.



Figure 2. Sketch map for input and output about the hidden nerve unit in RBF network.

and the *i*th output is  $r_i^q$ :

$$r_i^q = e^{-(k_i^q)^2} = e^{-\left(\sqrt{\sum_j (w \mathbf{1}_{j_i} - x_j^q)^2 \times b \mathbf{1}_i}\right)^2} = e^{-\left(\|w \mathbf{1}_i - x^q\| \times b \mathbf{1}_i\right)^2}.$$

By Gaussian transformation, the *i*th output from the *i*th neuron input of the hidden layer is

$$r_i^q = e^{-\left(k_i^q\right)^2} = e^{-\left(\sqrt{\sum_j \left(w \mathbf{1}_{ji} - x_j^q\right)^2 \times b \mathbf{1}_i}\right)^2} = e^{-\left(\left\|w \mathbf{1}_{i} - x^q\right\| \times b \mathbf{1}_i\right)^2}$$

Although the value of b1 can adjust the sensitivity of the function, in practice we commonly used another parameter *C* (called expansion constant). There are all kinds of methods to define the function about b1 and *C*. In MATLAB neural network toolbox, it sets

$$b1_i = 0.8326/C_i$$
.

And then the hidden layer neurons output is changed to:

$$r_i^q = e^{-\left(\frac{\left\|W1_i - X^q\right\| \times 0.8326}{C_i}\right)^2} = e^{-0.8326^2 \left(\frac{\left\|W1_i - X^q\right\|}{C_i}\right)^2}.$$

The values of C reflects response width of output for input. The bigger C takes, the better smoothness between two neurons we will get, caused by the response range of the hidden neurons to input vector expand with it.

The output is weighted summation of each hidden layer neurons output, excitation function using pure linear function. Then the neuron output  $y^q$  is

$$y^q = \sum_{i=1}^n r_i^q \times w2_i$$

RBF network training is divided into two steps, the

first step for the supervised learning training the weights W1 between input layers and hidden layer, the second step for supervised learning training the weights W2 between hidden layer and the output layer. Network training needs to provide input vector (X), corresponding target vector (T) and expansion constants of the radial basis function (C). The purpose of the training is to get the weights W1, W2, and the offset value b1, b2. (when the number of hidden units equals the number of input vector, we will take b2 = 0).

In RBF networks training, one of the key problems is to decide the number of neurons in hidden layer. In the past, we often make it equal with the number of the input vector. Apparently, for many input vector, too much hidden units is difficult to acceptable. Therefore we will improve the method. The basic principle is: 0 as a neuron started training, by checking the output error to make the network automatically increase neurons, after the training sample looping once, using the training sample which make the network produce have the maximum error as the weight vector  $W1_i$  to generate a new hidden neuron, then recalculating, checking the error of the new network, repeating this process until it reaches the required error or maximum number of hidden neurons, which we can see that RBF network has properties such as adaptation for determining the network construction and independence of initial weight value.

### 3. Application of the Radial Basis Network

### 3.1. Preparations for Neural Network

1) Training samples and test samples

We choose randomly five samples from No. 14 to No. 18 as test samples and others as the training samples. The sample are listed in **Table 1**.

2) The original data preprocessing

There are three kinds of pretreatment plans. The first is to normalize original data to between -1 and 1 by use of PRENMX function; the second is to normalize the original data to the expectation as 0 by Prestd function and the last one, the original data not being preprocessed.

# 3.2. Radial Basis Net Constructions, Training and Testing

1) Radial basis network construction

The number of input layer neurons in RBF network depends on the number of groundwater level and its main impact factors which are 5 here, and the number of the output layer neurons is set to be 1. The number of the hidden units can be adaptively determined by the use of MATLAB NEWRB function training network. The excitation function of the hidden units is RADBAS, the weighted function DIST, and the input functions NET-PROD. The excitation function of the output layer neu-

Sample number	River flow (m <sup>3</sup> /s)	The temperature (°C)	Saturation deficit (mbar)	Precipitation (mm)	Evaporation (mm)	Water level (m)	Note
1	1.5	-10	1.2	1	1.2	6.92	
2	1.8	-10	2	1	0.8	6.97	
3	4	-2	2.5	6	2.4	6.84	
4	13	10	5	30	4.4	6.5	
5	5	17	9	18	6.3	5.75	
6	9	22	10	113	6.6	5.54	
7	10	23	8	29	5.6	5.63	The training sample
8	9	21	6	74	4.6	5.62	sampte
9	7	15	5	21	2.3	5.96	
10	9.5	8.5	5	15	3.5	6.3	
11	5.5	0	6.2	14	2.4	6.8	
12	12	0.5	4.5	11	0.8	6.9	
13	1.5	11	2	1	1	6.7	
14	3	-7	2.5	2	1.3	6.77	
15	7	0	3	4	4.1	6.67	
16	10	10	7	0	3.2	6.33	Test sample
17	4.5	18	10	19	6.5	5.82	
18	8	21.5	11	81	7.7	5.58	
19	57	22	5.5	186	5.5	5.48	
20	35	19	5	114	4.6	5.38	
21	39	13	5	60	3.6	5.51	The training
22	23	6	3	35	2.6	5.84	sample
23	11	1	2	4	1.7	6.32	
24	4.5	_7	1	6	1	6.56	

Table 1. Monitored data on underground water level and impact factors.

rons is pure linear function PURELIN, the weighted function DOTPROD, and the input functions NETSUM [4,5].

2) Network training and testing

The level of the network training is related with the control error. It is listed in **Table 2** that the fitting error of network for the training samples and the generalizetion error for the test samples change with the mean square error. It is clear that the network is the best when the control mean-square error called goal equals 0.003. At this point, the maximum fitting error (relative error) of the network for 19 training samples is 1.6948%, and the generalization error (relative error) for 5 test samples is 3.7686%. Namely, applying the network to forecast, the error is expected to control within 4% which satisfies actual requirements.

3) The effect of the data pretreatment on RBF network

It is presented in **Table 3** that three methods of the original data preprocessing effect on network. By a large number of experiments, the method 1, 2, 3 get the best respectively when the *goal* is 0.003, 0.01 and 1. Then we

compare the effects of three networks. Consideration of the fitting and generalization error, method 3 gets worse obviously, methods 1 and 2 are similar, but method1 is better than method 2 overall.

### 3.3. Application Effect of the BP Network

Compared with radial basis network, we construct BP network to solve the problem. The process is as follows:

1) BP network construction

Taking three-layer network, the number of the input and output layer neurons is determined as 5 and 1 respectively. There has not been a uniform method how to determine the number of the hidden units. Here we follow the reference as 11.

The input and output functions (excitation function) for hidden units and the output units are respectively by means of hyperbolic tangent function and linear function, namely, TANSIG and PURELIN functions in MATLAB. Network is trained by using Powell-Beale conjugate gradient back propagation algorithm, namely TRAINCGB function in MATLAB. In this algorithm, the network

The mean square error (goal)	Number of training (epochs) -		Fitting error (%) (to the training sample)					
		14	15	16	17	18	The maximum	The maximum
0.1	4	2.4059	4.0485	0.3597	1.8798	0.8519		6.9383
0.01	12	4.5999	1.2495	1.9865	2.0323	0.6184	4.5999	2.067
0.005	13	4.0541	1.2349	2.7511	1.9714	0.6984	4.0541	1.8873
0.003	14	3.7686	1.9938	2.5896	2.667	0.8093	3.7686	1.6948
0.002	15	4.3711	0.59738	4.6132	2.9475	0.4611	4.6132	1.446
0.001	17	4.5395	2.4582	5.862	4.0232	0.9883	5.862	0.5531

Table 2. Relationship among fitting error, generalization error and mean squares error in RBF network.

Note: original data normalization to between -1 and 1.

#### Table 3. Effect for data pretreatment method to results of the network.

Data pretreatment	The mean square error (goal)		Fitting error (%) (to the training sample)					
method		14	15	16	17	18	The maximum	The maximum
1	0.003	3.7686	1.9938	2.5896	2.667	0.8093	3.7686	1.6948
2	0.01	3.3457	3.6511	1.6802	0.30445	3.1201	3.6511	2.2332
3	1	10.573	9.2367	4.3616	4.0191	8.493	10.573	12.526

1: Normalization between (-1,1); 2: (0 mean, Unit variance); 3: Not normalized.

Table 4. Experimental results for the dependence of BP net network on init	tial w	veight valu	ıe
--	--------	-------------	----

The mean square error (goal)	Serial number	The number of training (epochs)		Fitting error (%) (to the training sample)					
			14	15	16	17	18	The maximum	The maximum
0.001	1	89	3.6235	5.9782	15.834	0.2449	7.3573	15.834	1.039
	2	53	2.4167	8.4889	4.5997	2.748	3.0542	8.4889	1.2532
	3	94	4.2931	0.25671	10.633	1.4738	4.0307	10.633	1.1605
	4	70	2.912	5.9664	0.7478	3.487	3.5187	5.9664	1.2602
0.0001	1	117	3.5585	1.0414	4.28	8.3336	1.6329	8.3336	0.2606
	2	85	2.7315	7.2336	6.653	0.0136	2.1714	7.2336	0.2656
	3	159	3.1014	7.028	15.311	0.47124	10.368	15.311	0.3169
0.00001	1	300	2.7397	1.3411	15.893	1.5422	6.3726	15.893	0.0913
	2	154	3.0261	0.6460	6.4449	5.1405	1.7783	6.4449	0.1159
	3	132	2.2739	10.73	7.8112	2.4754	0.21642	10.73	0.0937

parameter is not adjusted along with the steepest descent direction (negative gradient direction) of the error surface, but is conjugate gradient direction, which has advantages of fast convergence and small footprint.

2) The effect analysis on BP network

In **Table 4**, it gives the results of three or four consecutive trainings and tests based on BP network when mean-square error *goal* equals 0.001, 0.0001 and 0.00001 respectively. It can be seen that firstly under the same mean-square error, results of training have great differences including the number of training, fitting error, generalization error which shows the initial weights of the BP network have a significant impact on the network effect; secondly compared with the result of RBF network in **Table 2**, BP network effect is clearly not as good as RBF network effect; and thirdly, the number of the training on BP network is much larger than on RBR network which shows the training speed of BP network is slower.

## 4. Conclusions

RBF network has properties such as adaptation for determining the network construction, independence of initial weight value on person, great speed, high accuracy and reliability and is deserved to be popularized to simulate and predict for groundwater regime. And this research shows that special attention is paid to the pretreatment of the original data in order to have an efficient network when we simulate and predict for groundwater dynamics based on RBF network.

At the same time, drawbacks on BP network such as artificiality for determining the construction, inferiority to RBF net on accuracy and speed of training and random of initial weight value to the outcome are all manifested after comparing RBF net and BP net. In addition, the BP network has many defects such as easiness to get the local minimum when learning and volatile, and redundant network connection or nodes. Many attempts have been done to improve it, but rarely desirable result is gotten. So we think that it should be very careful to select the BP network to simulate and forecast groundwater dynamics.

### REFERENCES

[1] S. Cong, "The Function Analysis and Application Study

of Radial Basics Function Network," *Computer Engineering and Applications*, Vol. 38, No. 3, 2002, pp. 85-87.

- [2] H. Demuth and M. Beale, "Neural Network Toolbox User's Guide," The MathWorks Inc., Natick, 1997, pp. 420-467.
- [3] P. D. Wasserman, "Advanced Methods in Neural Computing," Van Norstrand Reinhold, New York, 1993, pp. 334-366.
- [4] S.-Y. Zheng, Z.-B. Li and X.-A. Li, "Artificial Neural Network Method for Forecast of Underground Water Level," Northwest Water Lou Shuntian, Shi Yang, Systems Analysis and Design Based on MATLAB-Artificial Neural Network, XiDian University Publishing Company, Xi'an, 1998, pp. 210-256.
- [5] D. Xu and Z. Wu, "Systems Analysis and Design Based on MATLAB6.x-Artificial Neural Network," XiDian University Publishing Company, Xi'an, 2002, pp. 125-168.